# NARTAPE 165

INFORMATIVE DATA SHEET

# NARTAPE

## COMPOSITION

BACKING: polyvinylchloride (PVC) film ADHESIVE: natural rubber / hydrocarbonic resins / solvent CORE: recycled paper and paperboard

### SUITABLE FOR

Hand dispensers; sealing of recycled; cardboard boxes; flexographic machine print

### AVAILABLE COLOURS

Red - orange - black - white - yellow - green - light blue - dark blue - fluo orange

The excellent mechanical characteristics of resistance, plasticity and adhesion, combined with silent unwinding, make this tape suitable for all packaging applications and traditional uses.



BACKING THICKNESS 37 μm



DIRECTLY PRINTABLE



SILENT UNWINDING



WATER RESISTANT

MEDIUM WEIGHT PACKAGING



NAR S.P.A. Legnaro (PADOVA) ITALY www.nar-spa.com





COMPANY WITH ENVIRONMENTAL SYSTEM CERTIFIED BY DNV GL = ISO 14001:2015 = LEGNARO COMPANY WITH ENERGY MANAGEMENT SYSTEM CERTIFIED BY DNV GL = ISO 50001:2011= LEGNARO



INFORMATIVE DATA SHEET



	-		$\sim$	and the second s				$\mathbf{X}$		
	backing thickness µm	total thickness µm	adhesion N/cm	breaking load N/cm	elongation at break %	available colours	directly printable	silent unwinding	heavy weight packaging	medium weight packaging
NARTAPE 140	32	51	> 1,5 (WH)	> 45	> 48	Brown / white / transparent	•	•		•
			> <b>1,8</b> (BR TR)							
<b>NARTAPE</b> 165	37	56	> 1,8	> 50	> 48	Red / orange / black / white / yellow / green / light blue / dark blue / fluo orange	•	•		•
NARTAPE 190	60	81	> 1,8	> 68	> 80	Brown / transparent	•	•	•	

It is good practice to use the product within 12 months from purchase date (6 months if jumbo roll). The rolls must be kept in their original packing. Keep the product out of the light and protect from direct heat sources. The tape must be kept in a dry place, at humidity level below 65%, preferably at a temperature between 15° C and 25° C. If the storage temperature is different, restore the tape back to above level before using it.

The values in the informative data sheets are the average results of tests made on our standard production and are not legally binding. The aesthetic and technical features may be subject to some changes caused by ageing, even though the quality level of the product is maintained. Nar shall not be liable for direct damages or for any consequence arising from the misuse of the product. We suggest the verification of the product suitability to the specific condition of use.



Additional indications are available in the last edition of the booklet "Recommendation regarding choice, storing and use of pressure sensitive tapes" published by Federazione Gomma Plastica.